

DESCRIPTION

Johnstone's Trade Aqua Guard is our most durable Water Based Satin paint for interior wood and metal. Innovative surface protection technology provides the ultimate defence against scratches, wear & tear and greasy finger marks for a long-lasting finish. Johnstone's Trade Aqua Guard also has advanced application qualities, excellent hiding power and long-lasting whiteness*.

RECOMMENDED USES



- For interior wood and metal
- Apply by brush/roller
- Water Based
- Coverage up to 14 m²/l
- Recoat 4hrs

COLOUR RANGE

L Base and Z Base – 16,000 colours.

*Long-lasting whiteness is applicable to Brilliant White only.

FINISH

Satin Finish.

VOLUME SOLID

36%

COVERAGE



Up to 14m² per litre depending on the nature and porosity of the surface.

DRYING TIME



Touch Dry 1 - 2 hour.
Recoat after 4 hours.

TRANSPORTATION & STORAGE

PROTECT FROM FROST

To avoid the risk of spillage, always store and transport in a secure upright position.

Lift with care – gross weight does not exceed 8 kilograms.

THINNER

Clean water.

VOC CONTENT

EU limit value for this product (Cat A/d): 130g/l (2010).

This product contains max 80g/l VOC.



FILM THICKNESS

Wet 100 microns and Dry 35 microns.

KEY PROPERTIES

- Ultimate durability
- Resists grease, stains and scratches
- Outstanding opacity and long-lasting whiteness*

PREPARATION

All surfaces to be painted should be clean, dry and free from loose and flaking material. Rub down previously painted surfaces with fine waterproof abrasive paper and rinse thoroughly. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding. Prime bare wood with Johnstone's Trade Aqua Water Based Undercoat. Prime all other bare surfaces with the appropriate Johnstone's Trade primer. Apply one full coat of Johnstone's Trade Aqua water Based Undercoat to all correctly prepared and primed surfaces before application of Johnstone's Trade Aqua Guard Satin. Special precautions should be taken during surface preparation of pre-1960's paint surfaces over wood and metal as they may contain harmful lead. For more information and free Johnstone's Trade datasheets call 01924 354354 or visit www.johnstonestrade.com

APPLICATION



Ensure good ventilation during application and drying. Stir well. Easy to apply by brush or roller.

If more than one can of a colour is to be used in the same area, intermix before use. When attempting a wide colour change additional coats may be required. Do not apply in temperatures below 8°C.

CLEANING



Remove as much product as possible from application equipment before cleaning. Replace lid firmly. Clean equipment immediately after use with warm soapy water and rinse thoroughly. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

PRECAUTIONS

- Contains 1,2-benzisothiazol-3(2H)-one, 2-methylisothiazol-3(2H)-one and reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1). May produce an allergic reaction.
- Prolonged or repeated contact may dry skin and cause irritation
- Keep out of reach of children.
- If medical advice is needed, have product container or label at hand.
- Do not get in eyes, on skin or on clothing.
- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- IF SWALLOWED: Call a POISON CENTRE or doctor if you feel unwell.
- IF ON SKIN: Wash with plenty of water. Do not use solvent thinners or white spirit.
- Dispose of contents and container in accordance with all local, regional, national and international regulations.
- Safety data sheet available on request.

SIZES

1, 2.5 and 5 litre