

DESCRIPTION

Johnstone's Trade Professional Sterilisation Wash is a water based solution formulated for the treatment and control of mould, fungal and algal growth prior to painting. Suitable for interior and exterior treatment of walls, ceilings and masonry, including plaster, concrete, cement, render, brick and stone.

RECOMMENDED USES



For interior and exterior treatment of walls, ceilings and masonry including plaster, concrete, cement render, brick and stone.

SPECIAL PROPERTIES

Control of mould and algal growth.

COLOUR RANGE

Clear.

FINISH

Not applicable.

VOLUME SOLID

Not applicable.

COVERAGE



Johnstone's Trade Professional Sterilisation Wash will cover approximately 3-7 square metres per litre after dilution, depending on the degree of algal growth.

FILM THICKNESS

Wet: not applicable, dry: not applicable.

DRYING TIME



Allow 24 hours drying between treatments or before overpainting.

TRANSPORTATION & STORAGE

To avoid the risk of spillage, always store and transport in a secure upright position.

THINNER

Cleaner: Water.

VOC CONTENT

Not applicable.

PREPARATION

Remove all loose and flaking material and any heavy growth, moss etc, with a stiff brush.

KEY PROPERTIES

- Treats and controls mould, fungal & algal growth

PREPARATION

Remove all loose and flaking material and any heavy growth, moss etc. with a stiff brush.

APPLICATION



To avoid risks to man and the environment, comply with the instructions of use. **USE ONLY AS DESCRIBED ON LABEL.** Stir thoroughly before use. Dilute 1 part product with 4 parts clean water. Apply by brush working well into the affected areas. Allow to dry for 24 hours before washing/brushing off to remove all loose and flaking material. A second application should be carried out before painting is undertaken. Do not use on polished surfaces, carpets or textiles. Do not use externally in wet weather. For additional information and free Johnstone's Trade datasheets call 01924 354354 or visit www.johnstonestrade.com

CLEANING



Remove as much product as possible from application equipment before cleaning. Replace cap firmly. Clean equipment immediately after use with warm soapy water and rinse thoroughly. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

PRECAUTIONS

- Keep out of reach of children
- Avoid contact with skin and eyes
- Do not ingest
- If medical advice is needed have container or label to hand
- Please refer to Product Label & Safety Data Sheet (SDS) for hazard warnings and information on safe handling/use/transport/storage/disposal/emergency
- SDS available: www.johnstonestrade.com or call 01924 354354

SIZE

2.5 Litre