

## DESCRIPTION

A water-borne metal primer manufactured from high quality pigments and a special acrylic resin. Its excellent anti-corrosive and adhesion properties make it ideal for use on suitably prepared ferrous metals. Ideal for using as part of a system with Johnstone's Water Based Steel & Cladding Topcoat.

## RECOMMENDED USES



Primes suitably prepared ferrous metals, such as, steel, iron and prepared galvanised steel.

## SPECIAL PROPERTIES

Excellent anti-corrosive properties and adhesion to metal. Quick drying and low odour.

## COLOUR RANGE

White.

## FINISH

Matt.

## VOLUME SOLID

32%.

## COVERAGE



Johnstone's Quick Dry Metal Primer will cover at the rate of approximately 10 square metres per litre depending on the nature and porosity of the surface being painted.

## DRYING TIME



Touch dry in 2 hours.  
Recoat after 4 hours.

## TRANSPORTATION & STORAGE

To avoid the risk of spillage always store and transport in a secure upright position. PROTECT FROM FROST.

## THINNER

Water.

## VOC CONTENT

MEDIUM VOC CONTENT 8-24.99%  
VOCs (Volatile Organic Compounds) contribute to atmospheric pollution.

EU limit value for this product (Cat A/i):140g/l (2010).  
This product contains max 100g/l VOC.

## FILM THICKNESS

Wet: 100µm, dry: 34µm.

## SIZE

2.5 Litre.

## PREPARATION

All surfaces to be painted should be sound, clean, dry and free from grease, polish and loose or flaking material. Existing rust or millscale should be removed from iron and steel. Johnstone's Cleaner & Degreaser should be used to suitably clean the surface. Avoid the inhalation of dust. Wear a suitable face mask when dry sanding. Special precautions should be taken during surface preparation of pre-1960's paint surfaces over wood and metal as they may contain harmful lead. For further advice contact Technical Advisory on 01924 354354.

## APPLICATION



Stir well before use. Easy to apply by brush, roller or spray. Do not thin.

## CLEANING



Remove as much product as possible from application equipment before cleaning. Replace lid firmly. Clean equipment immediately after use with warm soapy water and rinse thoroughly. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

## PRECAUTIONS

- Harmful to aquatic life with long lasting effects.
- Contains reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one (EC no.247-500-7) and 2-methyl-2H-isothiazol-3-one (EC no.220-239-6) (3:1), 1,2-benzisothiazol-3(2H)-one and 2-methyl-2H-isothiazol-3-one. May produce an allergic reaction.
- Avoid release to the environment
- If medical advice is needed, have product container or label at hand.
- Keep out of reach of children
- Dispose of contents/container to a waste disposal site in accordance with local/national regulations
- Ensure good ventilation during application and drying.
- Do not get in eyes, on skin, or on clothing
- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- IF ON SKIN: wash with plenty of water. Do not use solvent thinners or White Spirit.
- IF SWALLOWED: Call a POISON CENTRE or doctor if you feel unwell.
- Safety data sheet available on request.